

BLAZER

DUNHURST

Weavers

World



Photographic fabric scans are not colour accurate. Always request actual fabric samples before ordering.

SPECIFICATIONS

Application	Upholstery
Composition	100% Pure New Wool - Non Metallic Dyestuffs
Width	140cm Minimum
Mass	460gm/m² +/-5% (645g/lin.min +/-5%)
Pattern Repeat	Plain

BLAZER

Abrasion Resistance	+50,000 Martindale Cycle
Colour Fastness	5 (ISO 105-B02: 1999)
To Light	
To Rubbing	Wet:4 Dry:4 (ISO 105-X12:2002)
Flammability	BS EN 1021 -1: 2006 (CIGARETTE), BS EN 1021-2: 2006 (MATCH) BS 7176:2007 LOW HAZARD, UNI 9175 CLASSE1 IM (FR PU 35KG) OPTIONAL - PLEASE SPECIFY WHEN ORDERING BS 5852:2006 SECTION R IGNITION SOURCES WHEN FR TREATED BS 7176:2007 MEDIUM HAZARD WHEN FR TREATED NOTE: FLAMMABILITY PERFORMANCE IS DEPENDENT ON FOAM
Cleaning Instructions:	VACUUM REGULARLY. PROFESSIONAL DRY CLEAN OR WIPE CLEAN

NOTE: Refer to SABS 726 - This specification calls for a minimum seam of 15mm and 4-5 stitches per cm.